



## Key Features

- High initial tack adhesive
- Rated for internal and external use
- Suitable for variety of display materials such as acrylic, ACM, Dense Foam and a wide range of plastics
- Operating temperatures of -40°C to +70°C
- Good resistance to temperature changes, weather and UV
- Paper release liner

## Stykra 130 white

Model No: **DS130**

The Stykra 130 is a cross linked PE foam tape with advanced acrylic adhesive. Suitable for bonding a variety of display materials such as ACM, Acrylic, Dense Foam, PVC foam board, card and other plastic materials. The Stykra 130 is designed for the mounting of lightweight signs and plaques to a wide range of materials in various locations.

## Construction

- White Paper Liner
- Crosslinked PE foam with pressure sensitive acrylic adhesive

Item	Unit	Spec	Test Method
Total Thickness	mm	0.8 (±0.1)	-
Elongation at break %	%	270	AFERA 4005
180 ° Peel Adhesion	N/cm	11	AFERA 4001
Tensile Strength	MPa	1200	AFERA 4004
Dynamic Shear	N/cm <sup>2</sup>	11	AFERA 4024
Tensile Adhesion	N/cm <sup>2</sup>	70	-
Temperature Resistance (long term)	°C	+70	-
Low Temp. Resistance	°C	-40	-
UV Resistance	-	Good	-

Stykra 130 must be stored in its original packaging in a clean and dry environment. The pressure sensitive adhesive has a recommended minimum application temperature of 15°C with a minimum pressure of 1 Bar. Low temperature application may increase the possibility of condensation which will reduce the final bond strength.

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Sign Trade Supplies will not be responsible for the product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended purpose.