



Key Features

- Permanent one side, removable other side
- Suitable for shortterm display and exhibition
- Clean peel removable on secondary side
- Operating temperatures of -20°C to +60°C
- Excellent resistance to temperature changes, weather and UV, salt water and alkalines.
- Amber Glassine release liner

Stykra 300 perm/peel

Model No: **DS300**

The Stykra 300 is a unique PE foam tape consisting of a 2 side construction. Side 1 features a high tack, permanent acrylic adhesive. Side 2 features a clean removable adhesive. The Stykra 300 has been designed specifically for the short term display of lightweight signs, plaques, POS and exhibition graphics. The clean removable adhesive makes it ideal for retail displays that require fast and easy application and removal.

Construction

- White Glassine Liner
- PE foam with permanent and temporary adhesive

| Item | Unit | Spec | Test Method |
|---------------------------|------------------|-------------------|-------------|
| Total Thickness | mm | 2.0 (±0.1) | - |
| Elongation at break % | % | 60 | - |
| Density | KGm ³ | 33 | - |
| Shear Strength | - | High / Medium Low | - |
| Suitable for outdoor use | - | No | - |
| Minimum Application Temp | °C | +15 | - |
| Temperature Resistance | °C | +70 | - |
| Low Temp. Resistance | °C | -40 | - |
| Adhesion to LSE materials | - | Medium / Low | - |

Stykra 300 must be stored in its original packaging in a clean and dry environment. The pressure sensitive adhesive has a recommended minimum application temperature of 15°C with a minimum pressure of 1 Bar. Low temperature application may increase the possibility of condensation which will reduce the final bond strength.

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Sign Trade Supplies will not be responsible for the product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended purpose.