



## Key Features

- Highly Aggressive rubber resin tape
- Extremely high performing “toffee tape”
- Excellent UV resistance
- Max operating temperature 80°
- Suitable for LSE twin flute material

## Stykra 450 ultra rubber resin

Model No: **DS450**

The Stykra 450 is a premium rubber resin tape with high performing properties. The Stykra 450 out performs standard “Toffee Tapes” with its unique formulation providing excellent UV resistance, improved shear performance and high peel adhesion strength. Designed for use in longer term correx bonding solutions such as estate agent boards and POS stands.

## Construction

- Solid rubber resin adhesive

Item	Unit	Spec	Test Method
Total Thickness	mm	1.0mm	-
Release liner	-	White Glassine paper	-
Peel Adhesion 180°	N/ 25mm	39.6	FTM 1
Shear Strength	10N/in <sup>2</sup>	>2995.0	FTM 8 @ 40°C
Softening Point	°C	120	°C Ring & Ball XLA QA502
Maximum Service Temperature	°C	80+	-
Minimum Service Temperature	°C	-10	-

Stykra 450 must be stored in its original packaging in a clean and dry environment with a shelf life of 12 months.

Unless stated otherwise all values given are average. All of the tapes in our range should be thoroughly tested on the substrates in the particular application they are intended for. Stykra will not be responsible for the product failure unless full testing has been completed. The customer has to decide on the tapes suitability for the intended purpose.